

# Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 22.06.2011

Revision: 21.06.2011

## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** RUBBERLAC
- **Relevant identified uses of the substance or mixture and uses advised against**  
No relevant identified uses-mixture of substances.
- **Application of the substance / the preparation** Bituminous waterproofing varnish
- **Details of the supplier of the safety data sheet**  
BM BITOUMINOUS MIXTURES A.E.  
PRODUCTION OF BITOUMINOUS MIXTURES  
15th km. Old National Road. Thessaloniki – Veria  
AG.ATHANASIOS THESSALONIKI  
Adress: P.O.BOX: 1715, 570 08 IONIA THESSALONIKI  
tel: +302310 710017  
FAX: 2310 710016  
e-mail: info@bitumix.gr
- **Further information obtainable from:** BM BITOUMINOUS MIXTURES A.E.
- **Emergency telephone number:** National Poisoning Centre

## 2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**  
 Xn; Harmful  
 R63-65: Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed.  
 R20: Harmful by inhalation.  
 R38: Irritating to skin.  
 R48: Danger of serious damage to health by prolonged exposure.  
 R10-67: Flammable. Vapours may cause drowsiness and dizziness
- **Information concerning particular hazards for human and environment:**  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**  
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- **Label elements**
- **Labelling according to EU guidelines:**  
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**  
 Xn Harmful
- **Hazard-determining components of labelling:**  
Toluene
- **Risk phrases:**
  - 10 Flammable.
  - 20 Harmful by inhalation.
  - 38 Irritating to skin.
  - 48 Danger of serious damage to health by prolonged exposure.
  - 63 Possible risk of harm to the unborn child.
  - 65 Harmful: may cause lung damage if swallowed.
  - 67 Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.06.2011

Revision: 21.06.2011

Trade name: RUBBERLAC

(Contd. of page 1)

- **Safety phrases:**

- 2 Keep out of the reach of children.
- 16 Far from sources of ignition. Smoking is forbidden.
- 23 Do not inhale gases/fumes/vapors/clouds.
- 36/37 Wear suitable protective clothing and gloves.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture: consisting of the following components.

- **Dangerous components:**

CAS: 108-88-3 EINECS:203-625-9	toluene Xn R48/20-63-65; Xi R38; F R11 R67 Repr. Cat. 3 Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	25-45%

### 4 First aid measures

- **Description of first aid measures**

- **General information:**

Take affected persons out into the fresh air. Seek immediate medical advice.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Generally the product does not irritate the skin.

- **After eye contact:** Rinse opened eye for several minutes under running water.

- **After swallowing:**

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Seek immediate medical advice.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Firefighting measures

- **Suitable extinguishing agents:** CO2, extinguishing powder, sand, foam

- **For safety reasons unsuitable extinguishing agents:**

Water with full jet

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.06.2011

Revision: 21.06.2011

Trade name: RUBBERLAC

(Contd. of page 2)

- Water spray
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**  
Fireproof suit with helmet ( EN 469,533,1486) and self breathing apparatus( EN 137)
- **Additional information**  
Collect contaminated fire fighting water separately. It must not enter the sewage system.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow to enter sewers/ surface or ground water.  
Do not allow to penetrate the ground/soil.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Prevent any seepage into the ground.  
Provide ventilation for receptacles.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

<b>Ingredients with limit values that require monitoring at the workplace:</b>	
<b>108-88-3toluene</b>	WEL Short-term value: 384 mg/m <sup>3</sup> , 100 ppm Long-term value: 191 mg/m <sup>3</sup> , 50 ppm Sk

(Contd. on page 4)

GE

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.06.2011

Revision: 21.06.2011

Trade name: RUBBERLAC

(Contd. of page 3)

- **Additional Occupational Exposure Limit Values for possible hazards during processing:**  
cas 64742-93-4 asphalt oxidized TWA 5mg/m<sup>3</sup>
- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.
- **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**  
Wear suitable gloves ( EN 374, 388, 407, 420)  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.
- **Eye protection:**



Safety glasses

- **Body protection:**  
Wear suitable protective clothing and chemicals proof boots ( EN 340, 365, 466, 467)



Use protective suit.

In case of release wear PVC apron( EN 345)

## 9 Physical and chemical properties

- |  |                       |
|--|-----------------------|
| · <b>Information on basic physical and chemical properties</b> |                       |
| · <b>General Information</b>                                   |                       |
| · <b>Appearance:</b>   |                       |
| Form:  | Liquid                |
| Colour:  | Black                 |
| · <b>Odour:</b>  | like organic solvents |
| · <b>Odour threshold:</b>                                      | Not determined.       |
| · <b>pH-value:</b>   | Not determined.       |
| · <b>Melting point/Melting range:</b>                          | Undetermined.         |
| · <b>Boiling point/Boiling range:</b>                          |                       |
| · <b>Flash point:</b>  | 21°C                  |

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2011

Revision: 21.06.2011

Trade name: RUBBERLAC

(Contd. of page 4)

· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	>300°C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Self-igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b> Lower: Upper:	Not determined. Not determined.
· <b>Vapour pressure:</b>	Not determined.
· <b>Density at 25°C:</b>	0.95 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Insoluble.
· <b>Segregation coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b> Dynamic: Kinematic:	Not determined. Not determined.
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Stable at environment temperature.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- Information on toxicological effects
- **Acute toxicity:**

· <b>LD/LC50 values relevant for classification:</b>		
<b>108-88-3toluene</b>		
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.

(Contd. on page 6)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.06.2011

Revision: 21.06.2011

Trade name: RUBBERLAC

(Contd. of page 5)

- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

### 12 Ecological information

- **Toxicity**
- **Acquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:** The product contains materials that are harmful to the environment.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**



Smaller quantities can be disposed of with household waste.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

- **Uncleaned packaging:**
- **Recommendation:**  
Disposal must be made according to official regulations.  
Packaging may be reused or recycled after cleaning.

### 14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.
- **Danger code (Kemler):** 30
- **UN-Number:** 1999
- **Packaging group:** III
- **Hazard label:** 3
- **Special marking:** Symbol (fish and tree)
- **UN proper shipping name:** 1999 TARS, LIQUID, ENVIRONMENTALLY HAZARDOUS

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2011

Revision: 21.06.2011

Trade name: RUBBERLAC

(Contd. of page 6)

· Tunnel restriction code D/E

· Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1999
- Label 3 · Packaging group: III
- EMS Number: F-E, S-E
- Marine pollutant: Yes Symbol (fish and tree)
- Proper shipping name: TARS, LIQUID

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 3
- UN Number: 1999
- Label 3
- Packaging group: III
- Proper shipping name: TARS, LIQUID

· Environmental hazards:

Product contains environmentally hazardous substances: naphtha (petroleum), hydrodesulfurized heavy

· Special precautions for user Warning: Flammable liquids.

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xn Harmful

· Hazard-determining components of labelling:

toluene

· Risk phrases:

- 10 Flammable.
- 20 Harmful by inhalation.
- 38 Irritating to skin.
- 48 Danger of serious damage to health by prolonged exposure.
- 63 Possible risk of harm to the unborn child.
- 65 Harmful: may cause lung damage if swallowed.
- 67 Vapours may cause drowsiness and dizziness.

(Contd. on page 8)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.06.2011

Revision: 21.06.2011

**Trade name: RUBBERLAC**

(Contd. of page 7)

**· Safety phrases:**

- 2 Keep out of the reach of children.
- 16 Far from sources of ignition. Smoking is forbidden.
- 23 Do not inhale gases/fumes/vapors/clouds.
- 36/37 Wear suitable protective clothing and gloves.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R11 Highly flammable.
- R38 Irritating to skin.
- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R63 Possible risk of harm to the unborn child.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

**· Department issuing MSDS:**

Sustchem Engineering LTD  
144, 3rd Septemvriou,  
11251

Athens Greece

Tel: +302108252510-14

e-mail: [info@suschem.gr](mailto:info@suschem.gr)

**· Contact:** BM BITOUMINOUS MIXTURES A.E.

GB